

Crimping Tools

Variocrimp 4, Variocrimp 16

	Variocrimp 4 Crimping tool for ferrules insulated and uninsulated from 0.25 mm ² – 4 mm ² /AWG 24 – 12 weight 400 g/0.882 lbs	Variocrimp 16 Crimping tool for ferrules insulated and uninsulated from 6 mm ² – 16 mm ² /AWG 10 – 6 weight 580 g/1.28 lbs
--	---	--



Description	Item No.	Pack.-unit pcs	Item No.	Pack.-unit pcs
Crimping tool Variocrimp 4, 0.25 mm ² – 4 mm ² /AWG 24 – 12	206-204	1		
Crimping tool Variocrimp 16, 6 mm ² – 16 mm ² /AWG 10 – 6			206-216	1

Application notes

- With the Variocrimp 4 built-in crimping pressure plates control the crimping force automatically for the conductor cross section used. With the Variocrimp 16 it is necessary to select the wire gauge on the tool before crimping.
- Each tool has only one crimping station for all the wire sizes handled.
- Uniform compact crimping from all four sides for high conductor retention.
- No need to center the conductor in the ferrule sleeve.
- Conductor and ferrule insertion possible from both sides (for left- and right handed).
- Built-in ratchet to guarantee complete crimping every time.
- Tools open automatically after crimping operation is complete.
- Comfortable handles for operator.



Introduce conductor with ferrule into crimping station.



Only for Variocrimp 16: Adjust conductor cross section with opened tool.



Squeeze handles until ratchet mechanism is released.



A perfect gastight crimp, both electrically and mechanically reliable.