






Clamp Spring - Spring type terminal blocks / WK series



W4K500



Pitch: 5.00mm

Approval	  	
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	24A
Wire range	2.5mm ²	
Solid wire (AWG)	28~12	
Stranded wire (AWG/mm ²)	28~12	
Rated surge voltage (UL/IEC/Max.)	1.6 / 2.5 / 4 KV	
Wire strip length	6~7mm	
Single Pole	Cat. No.	
	W4K500-04X	
End Cover	W4K500C	
Optional color	Cat. No.	
●	W4K500-04X	
●	W4K500-04X-GN	
●	W4K500-04X-RD	
●	W4K500-04X-BL	



●	W4K500-04X-BK
●	W4K500-04X-OR

Pole	Cat. No.
08	W4K500-08P
12	W4K500-12P
16	W4K500-16P
20	W4K500-20P
24	W4K500-24P
28	W4K500-28P
32	W4K500-32P
36	W4K500-36P
40	W4K500-40P
44	W4K500-44P
48	W4K500-48P
-	--
-	--

Optional color	Cat. No.
●	W4K500-XXP
●	W4K500-XXP-GN
●	W4K500-XXP-RD
●	W4K500-XXP-BL
●	W4K500-XXP-BK
●	W4K500-XXP-OR

TEL: +886-2-2908-0614

FAX: +886-2-2908-8549

E-mail: infor@dinkle.com.tw